



Desktop Retransfer Dual-sided Card Printer

R660



SEAORY R

Key Feature

Adopt high-resolution transfer dye-sublimation color printing technology.
 Standard 600dpi x 600dpi high resolution dual-sided printing
 Higher image quality and clear text, realizing professional-level printing effects
 Perfectly realize the entire card over-edge printing
 High printing speed engine
 All-metal movement, more stable continuous printing ability of card
 Support PVC, composite PVC, ABS, PET, PC and other materials to print high-quality cards
 Standard bend correction module
 With a 3.5-inch color touch-screen, the operation is more intuitive and convenient

Multi-function optional module

Dual interface card encoding module
 UHF chip card encoding module
 Contactless ID card encoding module
 Magnetic stripe card encoding module
 Electronic lock/mechanical lock of input hopper
 Electronic lock/mechanical lock of defective card slot
 Electronic lock/mechanical lock of ribbon door
 Lamination module

Consumables

Monochrome black ribbon: 100x60mm
 Full panel YMCKK ribbon: 500 prints/roll and 1000 prints/roll
 Full panel YMCKK ribbon: 500 prints/roll
 Full panel YMCKI ribbon: 500 prints/roll
 Full panel YMCKHs ribbon: 500 prints/roll
 Security YMCFK ribbon: 500 prints/roll
 Transparent retransfer film: 500 prints/roll and 1000 prints/roll

Value-added functions

Alarm for no card, defective card slot
 Manual feeding card on back end and recycling pending card
 Available to set the direction of output card



Dye-sublimation transfer printing technology

Professional printing software come with the printer

Specifications

Product Name	R660/Desktop Retransfer Dual-sided Card Printer
Printer Dimension	568mm × 272mm × 398mm (Length x Width x Height), 12Kg
Power	AC100~240V, 50/60Hz, 24V \approx 15A 360W
Print Speed	Monochrome black printing: 15-18s per card (single-sided), 27-30s per card (dual-sided) using ribbon saving technology Full-color YMCK Printing: 25s per card (single-sided), 42s per card (dual-sided)
Print Dimension	ISO CR80 (53.98mm×85.60mm) over-edge printing of the entire card
Print Resolution	600dpi × 600dpi
Print Method	Dye sublimation retransfer printing
Memory	256MB
Interfaces	Standard USB2.0 & Ethernet, WIFI (optional)
Card Material	PVC, composite PVC, ABS, PET, PC and other materials
Card Thickness	0.3-1.05mm (hopper adjustment required)
Input hopper capacity	200pcs (0.76mm)
Output hopper capacity	200pcs (0.76mm)
Defective card slot capacity	25pcs (0.76mm)
Buzzer	Yes
Indicator	Red and green two-color indicator
LCM Display	3.5 inch color touch-screen
Software	Driver: Support Windows XP/7/8/10/11, Windows Server 2003/2008/2012/2016, Linux, Mac OS, and NeoKylin, Kylin, UOS and other made-in-China operating system. Development Kit: Support Windows XP/7/8/10/11, Windows Server 2003/2008/2012/2016, Linux, and NeoKylin, Kylin, UOS and other made-in-China Operating System Card Design Software: iCARDE card design software, support Windows XP/7/8/10 operating systems
Warranty	Card printer: 3 years (artificial damage excluded) Print head: lifetime warranty
Operation Environment	Regular running temp: 15°C-30°C (59-86°F), 20%-65% RH non-condensing Lowest/Highest running temp: 0°C (32°F)/40°C (104°F), 20% to 65% RH non-condensing.
Storage Environment	Temp.: -5°C-70°C (23-158°F), 20% to 70% RH non-condensing and ventilation environment

